

CLIPPEDIMAGE= JP361276874A

PAT-NO: JP361276874A

DOCUMENT-IDENTIFIER: JP 61276874 A

TITLE: MAGNETIC ADHESIVE

PUBN-DATE: December 6, 1986

INVENTOR-INFORMATION:

NAME

TANUMA, ITSUO
FUKUURA, YUKIO
OZURU, HIROMI
HONDA, TOSHIO

ASSIGNEE-INFORMATION:

NAME

BRIDGESTONE CORP

COUNTRY

N/A

APPL-NO: JP60116758

APPL-DATE: May 31, 1985

INT-CL (IPC): C09J003/12;C09J003/14

US-CL-CURRENT: 524/425

ABSTRACT:

PURPOSE: The titled magnetic adhesive, consisting of a rubber based or acrylic adhesive composition containing ferromagnetic material, removable and reusable and having very strong power against shear force in the transverse direction.

CONSTITUTION: An adhesive obtained by incorporating (A) a ferromagnetic material, e.g. powder for ferrite magnets, with (B) a rubber based adhesive composition (containing a rubber component, tackifier component, inorganic filler, curing agent, etc.) or (C) acrylic adhesive composition (containing a copolymer of an acrylic and methacrylic monomers, isocyanate based compound). The compounding ratio of the components is preferably as follows; 100pts.wt. component (B) to 50~1,300pts.wt. component (A). The adhesive strength of the component (B) is desirably ≥ 0.04 kg/cm measured by the method according to JIS Z-0237.